


- 1. Proudly made in America at our ISO 9001:2008 registered facility.
- 2. Enclosure is constructed to Alabama Department of Transportation Lighting Load Center Drawing RLD002 dated 04/29/2011.
- 3. Handle, 3/4" dia. stainless steel pad-lockable hasp.
- 4. Lock, deadbolt, CORBIN style, keyed #2, main door with two keys each.
- 5. Latching, three point door with nylon rollers for top and bottom strikers.
- 6. Door stop rod, three position (90,120, and 180 degrees.
- Neoprene door gasket.
- 8. Top slopes 1/2 inch front to back.
- 9. Vent holes in front face rail, covered with aluminum screen, with top lid overhang to provide drip shield.
- 10. Vent holes in rear body, covered with aluminum screen, provided with drip shield.
- 11. Perforated vents on right and left side with vent hood per drawing.
- 12. Stainless steel hardware.
- 13. Continuous stainless steel door hinge.
- 14. Door switch bracket.
- 15. Photoelectric control with wire bracket vandal guard.
- 16. Engraved aluminum identification nameplate attached to door. One inch high lettering "ALABAMA DEPARTMENT OF TRANSPORTATION LIGHTING CONTROL CENTER *".
 - (* indicates letter designation of cabinet, A,B,C, or D). Engraved lettering to be delineated in black enamel.



SOUTI	HERN

FINISH:

MATERIAL: 5052H-32 ALUMINUM .125"

Southern Manufacturing 150 Hope Street Longwood, Fl. 32750 ph: 407-894-8851 fx: 407-831-1508

PROPRIETARY AND CONFIDENTIAL

The information contained in this drawing is the sole property of Southern Manufacturing. Any reproduction in part or as a whole without the written permission of Southern Manufacturing is prohibited.

ıg				SOUTHERN MFG. CO.	
		NAME	DATE		
,	DRAWN By:	SAS	06/27/2012	P/N: CA-60X36X16.5-MAIN-ASSY-3	
	CHECKED:			1/8" ALUMINUM 3R CABINET	
	MFG APPR:			60X36X16.5 BASE MOUNTED Rev: ()	
	Cust APPR:			Scale: 1:24 Sheet 1 of 21 SIZE A	