



NOTES

1. CABINET IS CONSTRUCTED FROM .125" THICK 5052H-32 ALUMINUM AND IS BASE MOUNTED.
2. CABINET HAS FOUR 66" TALL UNISTRUT RAILS MOUNTED ON THE REAR WALL AND TWO 60" UNISTRUT RAILS MOUNTED ON THE LEFT AND RIGHT SIDES.
3. CABINET HAS DOUBLE DOORS OF THE OVERLAPPING DESIGN ,RIGHT SIDE DOOR HAS LOUVERS , WITH A 14" X 20" FIBERGLASS AIR FILTER , THREE POINT LATCHING WITH A#2 LOCK , A 3/4" DIA. PAD LOCKABLE STAINLESS STEEL HANDLE , A THREE POSITION DOOR STOP , AND AN ALUMINUM NAME PLATE (DETAILS SUPPLIED BY CUSTOMER) ,LEFT DOOR HAS A THREE POSITION DOOR STOP.
4. BOTH DOORS HAVE A CONTINUOUS STAINLESS STEEL HINGE AND NEOPRENE GASKET ALL AROUND.
5. CABINET HAS A DOOR SWITCH BRACKET AND A SINGLE 4" REMOVABLE FAN PLATE.
6. CABINET HAS A 15" TALL RISER.
7. ALL HARDWARE IS STAINLESS STEEL.
8. CABINET IS RATED 3R AND IS UL LISTED.



**Southern Manufacturing**

501 Herndon Ave  
Orlando, Fl. 32803  
ph: 407-894-8851  
fx: 407-894-5373

MATERIAL:

FINISH:

DRAWN By:

CHECKED:

MFG APPR:

Cust APPR:

NAME

LAB

DATE

6/6/2011

**SOUTHERN MANUFACTURING CO.**

P/N: CA-72X72X24-SUBMITTAL

**SUBMITTAL DRAWING**

Scale: 1:32

Sheet 1 of 1

Rev: 0

SIZE **A**

PROPRIETARY AND CONFIDENTIAL

The information contained in this drawing is the sole property of Southern Manufacturing. Any reproduction in part or as a whole without the written permission of Southern Manufacturing is prohibited.